



ULTIMATE Grease

Part No: OPT-UG

14oz Tube, 10 Tubes Per Case

Avg. Weight Per Case: 9lbs

NLGI Grade: 2

Thickener Type: Calcium Sulfonate Complex

Color: Green

ULTIMATE grease is an auto, farm, marine and industrial grease with excellent shear stability, load carrying ability and water resistance. It is free of heavy metals and resists burning. It is formulated with oxidation inhibitors and has excellent resistance to rust and corrosion. It meets NLGI GC/LB requirements.

| TEST METHOD | DESCRIPTION | SPECIFICATIONS |
|-------------|--------------------------------------|----------------|
| D-217 | Cone penetration @ 77°F, Unworked | 276 |
| | Worked 60 Strokes | 279 |
| | Worked 10,000 Strokes | 287 |
| | Worked 100,000 Strokes | 296 |
| D-1831 | Roll Stability (% change) | 293 (+5.0) |
| D-1743 | Rust Protection | Pass |
| D-2265 | Dropping Point, °F(°C) | 550°F (288°C) |



Opti-Lube
 1195 S 1680 W, Orem, UT 84058
 801-491-3717 or 888-326-6789
 Fax. 801-805-8188
 Www.opti-lube.com

| TEST METHOD | DESCRIPTION | SPECIFICATIONS |
|-------------|------------------------------|----------------|
| D-2596 | 4-Ball EP Performance | |
| | Load Wear Index | 72 |
| | Weld Point, Kgf | 500 |
| D-2266 | 4-Ball Wear Protection | |
| | Scar Diameter, mm | 0.45 |
| D-2509 | Timken OK Load, lbs | 65 |
| D-3527 | Wheel Bearing Life Test, hrs | 120 |
| D-1264 | Water Washout | |
| | @175°F, % | 0.4 |
| D-4049 | Water Spray Off, % | 67 |
| D-1742 | Oil Separation, % Loss | .17 |
| | Base Oil Characteristics | |
| D-445 | Vis @ 40° cSt | 219 |
| D-445 | Vis @100° cSt | 18.7 |
| D-2161 | Vis @ 100°F SUS | 1000 |
| D-2161 | Vis @ 210°F SUS | 85 |
| D-2270 | Viscosity Index | 96 |
| | Low Temp Torqu-Wheel Bearing | |
| D-4693 | -40°C, N m | 9 |

Revision Date: 10/24/2016